

Version:  
December 1, 2022



**(JTM)**  
**Ceramic**  
**Discriminators**

**Token Electronics Industry Co., Ltd.**

**Taiwan:** No.137, Sec. 1, Zhongxing Rd., Wugu District,  
New Taipei City, Taiwan. 248012  
Tel: +886 2981 0109 Fax: +886 2988 7487

**China:** 17P, Nanyuan Maple Leaf Bldg., Nanshan Ave.,  
Nanshan Dist., Shenzhen, Guangdong, China. 518054  
Tel: +86 755 26055363

[Web: www.token.com.tw](http://www.token.com.tw)

[Email: rfq@token.com.tw](mailto:rfq@token.com.tw)



## ▶ Product Introduction

### Introduction (JTM)

#### Characteristics :

- Dimensions: (6.0 × 6.0 × 3.0) Unit: mm.
- Storage temperature range: -40°C to +85°C.
- Operating temperature range: -20°C to +80°C.
- Center Frequency: 455±2 (KHz), 447.5±1.5 (KHz), 429.0±2.0 (KHz).
- Available IC: CXA1483M, CXA1484, CXA1184M, CXA3117N, LA8610, NE605, MC3371, TA31136, TA31142, TA31143, TA31147, TA8104, TA8103F.

Ceramic discriminator for communication (JTM) is compatible to Murata CDB/CDBC/CDBM. (JTM) For Communication consists of wide band piezoelectric resonator. It is ideal for mobile communication equipment due to its small size and light weight. Standard line includes products for a wide range of applications, from cordless telephones to cellular telephones, making non-adjustment and shrinking of the detection circuit possible.


Token (JTM) including features with small in size and lightweight, realize non-adjustment in detection circuit, high sensitivity and stability, wide range of standard products are available for various ICs, operating temperature range: -20°C to +80°C and storage temperature range: -40°C to +85°C.

Contact us with your specific needs. For more information, please link to Token official website "[Ceramic Discriminator](#)".



## ► Dimensions

### Dimensions (Unit: mm) (JTM)



## ► Technical Characteristics

### Technical Characteristics - Group A (JTM)

Part Number	Center Frequency (fo) (KHz)	Recovered Audio 3dB BW (KHz)Min.	Recovered Audio Output (mV)Min.	Distortion Factor (At fo) (%)Max.	Applicable IC
JTM455C18	455±2	±3.0	180±40	2.0	MC3371
JTM455C24	455±2	±4.0	100±40	2.0	TA31136
JTM455C28	455±2	±4.0	40±20	3.0	TA31142
JTM455C29	455±2	±4.0	125±30	2.5	NE605
JTM455C32	455±2	±4.0	40±20	3.0	TA31143
JTM455C47	455±2	-	140±20(fo) 140±20(fo±4.8)	-	TA31147
JTM455C50	455±2	±4.0	64±6.4	4.0	CXA3117N

### Technical Characteristics - Group B (JTM)

Part Number	Resonant Frequency (Fr)(KHz)	Antiresonant Frequency (Fa)(KHz)	Band Width Fa-Fr(KHz)	Resonant Resistance (Ω)Max.	Capacitance pF±20%	Applicable IC
JTM455C2	447.5±1.5 (at  Z =2.05kΩ)	463.0±1.5 (at  Z =10kΩ)			140	TA8104
JTM455C3		455.0±1.5	48.0±5.0	70	600	CXA1184M
JTM455C4		470.0±1.0	43.0±2.0	300	140	LA8610
JTM455C10	429.0±2.0		51.0±5.0	70	580	TA8103F
JTM455C15		463.5±1.0	43.0±2.0	300	140	CXA1483M
JTM455C25		465.0±1.5	45.0±4.0	300	135	CXA1484

## ► Order Codes

### Order Codes (JTM)

JTM455C24	P
Part Number	Package

▶ **General Information**

**Advantage of Token Piezoelectric Ceramics**

Token Electronics had been able to develop specialized piezo materials which when combined with an advance design have resulted in a complete line of practical, inexpensive piezo devices for entertainment and communications applications.

Token reliably deliver high-quality components according to the each customer special needs with respect to performance, costs, and technology modifications.

For marketing discontinuations or sourcing activities concerning Piezoelectric **Discriminator** products, you are encouraged to contact our Sales Department so the request can be properly directed within Token.

