

Version:
January 12, 2017



(NTK)
**High Voltage
Network Dividers**

Token Electronics Industry Co., Ltd.

Taiwan: No.137, Sec. 1, Zhongxing Rd., Wugu District,
New Taipei City, Taiwan, R.O.C. 24872
Tel: +886 2981 0109 Fax: +886 2988 7487

China: 12F, Zhong Xing Industry Bld., Chuang Ye Road,
Nan Shan District, Shen Zhen City,
Guang Dong, China 518054
Tel: +86 755 26055363; Fax: +86 755 26055365

[Web: www.token.com.tw](http://www.token.com.tw)

<mailto:rfq@token.com.tw>



▶ Product Introduction

Token High Voltage Resistor Network Dividers can be customized to order.

Specifications :

- Resistance Range: $1K\Omega \sim 10G\Omega$.
- Resistance Tolerance: $\pm 1\% \sim \pm 30\%$.
- Thick film on Aluminum $> 96\% Al_2O_3$.
- High Voltage Withstanding: Up to 30 ~ 50KV.
- Low VCR: 1ppm / 5ppm / 10ppm upon request.
- Temperature Range: $-55^\circ C \sim +125^\circ C$ (higher temp. upon request).
- Low TCR Available: 250 ppm/ $^\circ C$. (ppm/ $^\circ C$ or tighter upon request).

Features :

- Flat style, Low Resistor Noise.
- Non Inductive Design.
- Divider Design upon Request.
- Pb-free Production: Meet RoHS.
- Different Coating Available: Glass / Epoxy resin / Silicon.
- Solderable Leads (Tin coated copper leads): Type $\Phi 0.5$ ($\Phi 0.6$ / $\Phi 0.8$ upon request).

RoHS-compliant resistor network, high-value high-voltage resistors and potential dividers in a wide variety of configurations are now available from Token Electronics as custom versions of its standard ranges of resistive products.

This advanced film resistor technology provides the performance characteristics required by the precision input signal circuits of both bench-type and laboratory digital instruments. In addition to requiring less board space, these compact voltage network dividers deliver higher performance than selected discrete resistor sets and thin-film dividers.

Manufactured using advance thick-film technology from existing tooling ensures fast turnaround of samples prior to low to medium volume in-house production. These custom dividers are ideal for high performance voltage division applications in medical equipment, laboratory equipment, analytical instruments, etc. The custom high voltage network divider can be supplied in various packages and packaging materials including glass, epoxy resin, silicon options.

By applying this technology to the low-profile, single-in-line package configuration, the Type (NTK) Custom SIP Resistor Networks are available with a combination of features. Which include: Low TCR 250 ppm/ $^\circ C$ (100 ppm/ $^\circ C$ or tighter upon request), operating temperature range $-55^\circ C \sim +125^\circ C$ (higher temperature upon request), flat style, non-inductive, low noise, and also custom divider design.


For complete information on quantity price and delivery, please contact our Sales Office, or link to Token official website "[High Voltage Resistors](http://www.token.com.tw)" to get more information.



▶ NTK-A Electrical Parameters

Electrical Parameters (NTK-A)

Type	PIN	Resistance Value (Ω)		Resistance Tolerance	Pressure parameters	Rated Power (W)
NTK-A	1~2	R1	30M	K ($\pm 10\%$)	4KV Min.	0.6W Min.
	2~3	R2	30M	K ($\pm 10\%$)	4KV Min.	0.6W Min.
	3~4	R3	1M	J ($\pm 5\%$)	500V Min.	0.3W Min.
	4~5	R4	800M	K ($\pm 10\%$)	10KV Min.	1W Min.




High Voltage Divider Network (NTK-A) Series Dimensions



▶ NTK-B Electrical Parameters

Electrical Parameters (NTK-B)

Type	Serial Number	Resistance Value (Ω)	Rated Power	Resistance Tolerance	Temperature Coefficient	Operating Voltage
NTK-B	R1	52M	5W	$\pm 5\%$	$\pm 250\text{PPM}/^\circ\text{C}$	8500V
	R2	10K	-			-
	R3	10K	-			-
	R4	16M2	4W			4200V
	R5	17M3	3W			4400V
	R6	3M3	1W			800V
	R7	8K	-			-



High Voltage Divider Network (NTK-B) Series Dimensions

