

Version:
December 1, 2022



Typical RoHS Reflow Profile

[Web: www.token.com.tw](http://www.token.com.tw)

[Email: rfq@token.com.tw](mailto:rfq@token.com.tw)

Token Electronics Industry Co., Ltd.

Taiwan: No.137, Sec. 1, Zhongxing Rd., Wugu District,
New Taipei City, Taiwan. 248012
Tel: +886 2981 0109 Fax: +886 2988 7487

China: 17P, Nanyuan Maple Leaf Bldg., Nanshan Ave.,
Nanshan Dist., Shenzhen, Guangdong, China. 518054
Tel: +86 755 26055363




▶ Typical RoHS Reflow Profile

Typical RoHS Reflow Profile

All Token RoHS-compliant parts are backward compatible with tin-lead soldering processes. Soldering temperature must be greater than 230°C to ensure proper melting of lead-free solder.

For all soldering methods, the optimal reflow profile for a circuit board assembly is dependent on the solder material, solder amount, flux, temperature limit of each soldered component, heat transfer characteristics of the circuit board and component materials, and the layout of all components. The temperature versus time limitation of the least robust component of the circuit board assembly ultimately may determine the actual temperature profile that must be used. For these reasons, Token does not specify soldering profiles for our components.



Typical RoHS Reflow Profile